
## **Technical Data Sheet RG59/U Type SDI Coaxial Cable**

# WEST PENN WIRE



2833 West Chestnut Street Washington, PA 15301 Toll Free: (800) 245-4964 Fax: (724) 222-6420 www.westpenn-wpw.com

Mhz

db/100ft

819 **PART NUMBER:** 

**DESCRIPTION:** RG59/U - 1 Conductor 20AWG Solid, 100% Aluminum Foil + 95% Tinned copper braid and an

overall PVC Jacket.

**NEC RATING: CMR** 

APPROVALS: (UL) C(UL) Listed or c(ETL)us Listed

**APPLICATION:** Indoor for: Pro-Video, SDI, Digital Audio, CCTV and CATV

#### **Construction Parameters:**

Conductor 20 AWG Bare Copper

Stranding Solid

Insulation Material Gas Injected Polyethylene

.142" Nom. Insulation Thickness

Number of Conductors 1 Center Conductor

Shield 100% Al. Foil + 95% Tinned Copper Braid

Jacket Material 0.232" Nom. Overall Cable Diameter 29 Lbs/1M' Nom. Approximate Cable Weight

Flame Rating UL 1666

## **Electrical & Environmental Properties:**

Temperature Rating	-20deg C to 60deg C	1	.28
Max. Capacitance Between Conductors @ 1 KHz	16.2 pf/ft Nom.	10	.66
Velocity of Propagation	82% Nom.	71.5	1.93
Impedance	75 ohms Nom.	135	2.62
DC Resistance per Conductor @ 20deg C	10.1 Ohms/1M' Nom.	360	4.30
Jacket Color	Black		
	Min. Orders:	720	6.23
	Red, Green, Blue	1000	7.49
	White, Yellow, Violet,	2250	11.19
	Brown, Orange	3000	13.23
RoHS Compliant	Yes	4500	16.40

## **Mechanical Properties:**

SRL: 5-1600Mhz -23dB Max. Recommended Pull Tension 1.6Mhz-4.5Ghz 47 lbs. -21dB Min. Bend Radius (Install) 2.5"

## **Connectors and Accessories**

75 ohm BNC Crimp CN-BM74-32 Crimp Tool: TL-104 Strip Tool: TL-7503 1 Pc. Compression BNC 75 ohm CN-CSBNC-59 Comp. Tool: TL-SNSA Strip Tool: TL-CSST **Double Bubble Compression** CN-DB59BNCHD Comp. Tool: TL-SNSA Strip Tool: TL-CPLRBC Compression RCA CN-CSRCA-59 Comp. Tool: TL-SNSA Strip Tool: TL-CSST

Specification Issue Date: 7/06

This document is the property of West Penn Wire. The information contained herein is considered Proprietary and not to be reproduced by any means Without written consent of West Penn Wire

Standard Lengths are 1000ft. The Jacket is sequentially footmarked. The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.